



# **THERMAL**

*Circuit Protection*



## **SELECTOR GUIDE**

## THERMAL CIRCUIT BREAKERS

	 <b>C1005B-Series</b>	 <b>CTB-Series</b>	 <b>CMB-Series</b>	 <b>CLB-Series</b>
<b>Number of Poles</b>	1	1	1	1
<b>Actuator Style</b>	rocker, lighted rocker	rocker	pushbutton	pushbutton
<b>Max Current &amp; Voltage Ratings</b>	7 to 16A, 125-250VAC, 32VDC	3 to 16A, 125-250VAC, 50VDC	3 to 20A, 125-250VAC, 32 VDC	3 to 60A, 125-250VAC, 32 VDC
<b>Max Interrupting Capacity</b>	1000A	1000A	2500A@32VDC	2500A@32VDC
<b>Available Circuits</b>	series trip manual reset	series trip manual reset	series trip manual reset	series trip manual reset
<b>Terminal Options</b>	.250" tab, solder lug	.250" tab	.250" tab, .250" tab with 90° bend, screw terminal, screw terminal with 90° bend	.250" tab, .250" tab with 90° bend, screw terminal, screw terminal with 90° bend
<b>Mounting Method</b>	front panel snap-in	front panel snap-in	threaded bushing, front panel snap-in	threaded bushing, front panel snap-in
<b>Operating Temperature</b>	-10°C to 65°C	-10°C to 60°C	-10°C to 60°C	-10°C to 60°C
<b>Agency Approvals</b>	UL, cUL, TUV	UL, cUL, VDE, CE	UL, cUL, CSA, TUV, CE, UL 1500 / ISO 8846 for ignition protection / marine	UL, cUL, CSA, TUV, CE, UL 1500 / ISO 8846 for ignition protection / marine

*\*Manufacturer reserves the right to change product information without prior notice*